



## Model 48-4 SSK

Carbon Steel

## Sand Media Filtration

### Features

- Filter tanks are constructed out of carbon steel
- Skid is constructed out of carbon steel with integral forklift slots
- Carbon steel inlet, outlet and backwash manifolds
- AC and DC powered automatic filter backwash controller that allows for timed, pressure differential or manual backwash intervals
- Equipped with continuous acting air vents
- System can stand alone or be used in combination with additional filtration equipment



### Technical

- Consists of four 48" filter tanks
- Fitted with air vents and pressure gauges
- Tanks provide 50 square feet of filtration area
- Inlet and outlet manifold connection are 8" Victaulic
- Backwash manifold connection is 4" female NPT
- 8" media loading ports
- 8" media removal ports
- 80 psig working pressure
- 500 lbs. of gravel per tank
- 1300 lbs. of sand per tank
- Most effective backwash rate is 190 GPM min.
- Footprint: ~270" long by ~72" wide
- Pressure sustaining valve to aid in backwash operation
- Solar battery charger for DC operation in remote locations

**Maximum PSI: 80**  
**Maximum Flow: up to 1000 GPM**

### Available Accessories

- Power Prime Pumps
- Spill Guard Containment berms
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



### Rain for Rent

P.O. Box 2248  
Bakersfield CA 93303  
800-742-7246  
661-393-1542  
FAX 661-393-1542  
www.rainforrent.com  
info@rainforrent.com

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and Specifications are subject to change without notice.