



Model PF 1000

Particulate Filter

Features

- Single cartridge filtration
- Ninety (90) replaceable cartridge filter for high removal efficiency
- Replaceable filtration cartridges from 100 to .5 micron nominal rating
- No moving parts
- Skid or trailer mounted

Technical

- Units fitted with bleed valves and pressure gauges
- Initial pressure drop is less than 5 psi at 1000 gpm
- System can stand alone for sediment removal or be used in combination with media vessels
- Multiple cartridge filters provide large surface area for longer service life
- Trailer mounted unit has leveling jacks
- Skid footprint: 47" long x 41" wide x 88" high
- Skid dry weight: 1,400 lbs
- Trailer footprint: 200" long x 88" wide x 98" high
- Trailer dry weight: 3,250 lbs



Maximum PSI: 150
Maximum Flow: 1000 GPM

Material Specifications

- Chambers constructed of carbon steel
- 6" flange, 150# inlet and outlet
- Each cartridge filter chamber holds ninety 40" double open ended cartridges with 2-1/2" OD and 1" ID
- Maximum operating temperature: 250 degrees
- Maximum operating pressure: 150 psi
- Recommended working pressure: 75 psi

Available Accessories

- Power Prime Pumps
- Spill Guard Containment berms
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



Rain for Rent
P.O. Box 2248
Bakersfield CA 93303
800-742-7246
661-393-1542
FAX 661-393-1542
www.rainforrent.com
info@rainforrent.com

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and Specifications are subject to change without notice.